Product Name Premium PVA wood glue EUGB/EN

Revision Date May.24.2018***

Revision Number 2***.01*** Issuing date May.24.2018***

<u>SECTION 1: Identification of the substance/mixture and of the company/undertaking</u>

1.1. Product identifier

Product Name

Premium PVA wood glue

REACH Registration Number

This product is a mixture and therefore not directly subject of the registration requirements under REACH.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use

1.3. Details of the supplier of the safety data sheet

Adhesives Online, Division of The Corzak Group Ltd., The Oakley, Kidderminster Road, Droitwich, Worcestershire, WR9 9AY. Tel: 0330 094 8448 E: enquiries@adhesivesonline.co.uk

Tel: 0330 094 8448

SDS Contact (email of responsible person)

enquiries@adhesivesonline.co.uk

1.4. Emergency telephone number

+44 (0) 330 094 8448. Office hours:

Mon - Thurs. 9am - 5pm, Fri. 9am - 4.30pm

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation 1272/2008/EC (CLP)

Not a hazardous substance or preparation according to Regulation 1272/2008 (CLP)

2.2. Label elements

EC Hazards EUH208 - Contains 1,2-Benzisothiazol-3(2H)-one; 2-Methyl-2H-isothiazol-3-one.

May produce an allergic reaction.

EUH210 - Safety data sheet available on request

2.3 Other Hazards The mixture does not meet the criteria for PBT / vPvB according to REACH,

Annex XIII

Statements of hazard Frequent contact can lead to skin and eye irritation, especially if product is allowed

to dry out

Observe the usual precautions when handling chemicals.

Product Name Premium PVA wood glue EUGB/EN

Revision Date

May.24.2018*** 2***.01*** May.24.2018*** **Revision Number** Issuing date

SECTION 3: Composition/information on ingredients

Chemical characterization Water-borne polymer emulsion. Basis: Vinyl acetate Contains film-forming

helping agents***

3.1. Substances not applicable

3.2. Mixtures see Chemical characterization

Components	CAS-No	EC-No.	Identification Number	Percent %
1,2-Benzisothiazol-3(2H)- one	2634-33-5	220-120-9	613-088-00-6	0.01
2-Methyl-2H-isothiazol-3-one	2682-20-4	220-239-6		0.01
2-(2-Butoxyethoxy) ethyl acetate	124-17-4	204-685-9	none***	2

Components	1272/2008/EC (CLP)	Hazard Statements
1,2-Benzisothiazol-3(2H)-one	Acute oral toxicity - Category 4	H302
, ,	Skin corrosion / irritation - Category 2	H315
	Serious eye damage / eye irritation - Category 1	H318
	Skin sensitization - Category 1	H317
	Acute aquatic toxicity - Category 1	H400
	Chronic aquatic toxicity - Category 2	H411
	Acute inhalation toxicity - Category 2	H330
2-Methyl-2H-isothiazol-3-one	Acute oral toxicity - Category 3	H301
	Acute dermal toxicity - Category 3	H311
	Acute inhalation toxicity - Category 2	H330
	Skin corrosion / irritation - Category 1B	H314
	Acute aquatic toxicity - Category 1	H400
	Serious eye damage / eye irritation - Category 1	H318
	STOT SE - Category 3	H335
	Chronic aquatic toxicity - Category 2	H411
	Skin sensitization - Category 1A	H317
2-(2-Butoxyethoxy) ethyl acetate	Not a dangerous substance according to GHS	

SECTION 4: First aid measures

4.1. Description of first aid measures

General Information Remove contaminated, soaked clothing immediately and dispose of safely***

Inhalation Move to fresh air. If symptoms persist, call a physician.

Skin Wash off with soap and water. If symptoms persist, call a physician.

Eyes Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Call a physician immediately.

Product Name Premium PVA wood glue EUGB/EN

Revision Date May.24.2018***

Revision Number 2*** 01*** Issuing date May.24.2018***

Ingestion If swallowed, seek medical advice immediately and show this container or label. If

conscious, drink plenty of water. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Dry powder, Carbon dioxide (CO2), Water spray***

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of Carbon monoxide

Carbon dioxide (CO2)

Combustion gases of organic materials must in principle be graded as inhalation poisons

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

Environmental precautions

Dike and collect water used to fight fire.***

Other Information

This is a water-based product and presents no particular fire or explosion hazard.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Contaminated surfaces will be extremely slippery. Avoid contact with the skin and the eyes.

6.2. Environmental precautions

Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Contaminated equipment (brushes, rags) must be cleaned immediately with water. Dispose of in accordance with local regulations.

6.4. Reference to other sections

Consult trained personnel. Consider the information for "Personal Protection" in chapter 8 of this Safety Data Sheet.

Product Name Premium PVA wood glue EUGB/EN

Revision number 2***.01*** Revision Date May.24.2018***
Issuing date May.24.2018***

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Take off all contaminated clothing immediately Wash contaminated clothing before re-use

Advice on safe handling

Product may contain hazardous volatile ingredients which could accumulate in the unvented headspace of drums or containers. Open containers in ventilated area. Do not breathe vapour. During longer storage small amounts of carbon monoxide may form. To the best of our knowledge, no OEL (occupational exposure limit) is exceeded during the intended use. Containers/tanks may only be entered after thoroughly executed ventilation while considering national regulations and international standards for inspection of containers/tanks. In any case of doubt a measurement of the CO concentration is necessary.

Incompatible products

Materials that react with water

Protection - fire and explosion:

No special protective measures against fire required.

Reduce the release of the substance or mixture to the environment

See Section 8: Environmental exposure controls

7.2. Conditions for safe storage, including any incompatibilities

Material storage

Protect from frost. To maintain product quality, do not store in heat or direct sunlight. Keep at temperatures between 5 °C and 35 °C (40 °F and 95°F). Agitate before use***

Incompatible products

Materials that react with water

Technical measures/Storage conditions

Keep tightly closed in a dry and cool place. No special technical protective measures required.

German storage class

12: Non-combustible liquids

7.3. Specific end use(s)

None known

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EC Exposure Limit Values

No exposure limits established.

National occupational exposure limits

No exposure limits established

DNELs The product is exempt from REACH registration

PNECs The product is exempt from REACH registration

4 of 8

Product Name Premium PVA wood glue **EUGB/EN**

Revision Number 2***.01*** **Revision Date** May.24.2018***

May.24.2018*** Issuing date

8.2. Exposure controls

Engineering measures Provide adequate ventilation. Where reasonably practicable this should be

achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment

General advice Avoid contact with skin and eyes.

Wash hands before breaks and at the end of workday. When using, do not eat, Hygiene measures

drink or smoke. Take off all contaminated clothing immediately Wash

contaminated clothing before re-use

Eye protection Safety glasses.***

Hand protection Chemicals resistant gloves

Nitrile rubber *** Suitable material

Type Nitril (Company KCL) or comparable article;

or refer to glove manufacturer's recommendation

Evaluation according to EN 374: level 6 **Material thickness** Approx. 0.1 / 0.4 mm***

Break through time > 480 min

Environmental exposure controls

Do not discharge into the drains/surface waters/groundwater

Environmental Precautions

Should not be released into the environment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form liquid Color white Odor sweet

Autoignition Temperature Not determined

Melting point/range ~0° C ~ 100 °C Boiling point/range

Density 0.95 - 1.1 g/ml @ 25°C

Method ISO 2811-3

2.8 - 3.4pН Method ISO 976

Viscosity 12000 - 18000 mPa*s @ 25°C Method Brookfield Visc. RVT Sp. 5 / 20 r.p.m.

24 hPa @ 20°C Vapor pressure

Water solubility miscible

The product was not tested for properties not listed on the SDS*** 9.2. Other information

Product Name

Premium PVA wood glue

EUGB/EN

Revision Number

2***.01***

Revision Date Issuing date May.24.2018*** May.24.2018***

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage conditions.***

10.2. Chemical Stability

No decomposition if stored and applied as directed.

10.3. Possibility of hazardous reactions

No hazards to be especially mentioned.

10.4. Conditions to avoid

Do not freeze.

10.5. Incompatible Materials

Materials that react with water

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute Toxicity:

LD50/oral/rat

> 5000 mg/kg

Method:

EC 440/2008, B.1 (corresponding to OECD 401)

Skin Irritation:

non-irritant

Method:

EC 440/2008, B.4 (corresponding to OECD 404)

Species:

rabbit

Eye irritation:

non-irritant

Method:

EC 440/2008, B.5 (corresponding to OECD 405)

Species:

rabbit eye

The toxicological data given are determined by analogy.

SECTION 12: Ecological information

Biodegradation:

> 80%

Method:

Zahn-Wellens-Test OECD 302 B

Toxicity to bacteria

EC0: ~ 1000 mg/l

Method:

OECD 209

Chemical Oxygen Demand (COD)

~ 1000 mg/g

Method:

calculated

Acute fish toxicity

LC50: > 500 mg/l

Durations: (hours)

05050

Method: Species: OECD 203 zebra fish

Product Name: EUGB/EN

Premium PVA Revision Date May.24.2018*** wood glue. May.24.2018***

Revision Number 2*** 1***

Ecological data are determined by analogy.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product informationDisposal required in compliance with all waste management related state and

local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal. Diluted solution may be introduced into a biological

purification plant, with permission of the responsible authorities.

Uncleaned empty

packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Regulations concerning reuse or

disposal of used packaging materials must be observed.

European Waste Catalogue Allocation of a waste code number, according to the European Waste Catalogue

(EWC), should be carried out in agreement with the regional waste disposal

company.

SECTION 14: Transport information

ADR/RID Not regulated

ADN Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Water Hazard Class (WGK): WGK Class

WGK Source Classification according to AwSV***

15.2 Chemical Safety Assessment

Chemical Safety Assessment (CSA) is not required

SECTION 16: Other information

For further information, see:

For more information, consult the Technical Data Sheet. For more information, other material safety data sheets or technical data sheets please contact our head office on 0330 094 8448.

Product Name

Premium PVA wood glue

EUGB/EN Revision Date May.24.2018***

Revision Number

2***.01***

Issuing date May.24.2018***

Other Information:

· Traces of residual monomers can be found in the product:

Changes against the previous version are marked by ***

Training advice

Make sure that employees are aware of the hazards / risks as detailed on this Safety Data Sheet.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Adhesives Online generated data and public sources deemed valid or acceptable. The absence of data elements required by ANSI or 1907/2006/EC indicates that no data meeting these requirements is available.

Further information

This information is based on our present state of knowledge. It shall describe our products regarding safety requirements and shall not be construed as a guarantee or statement of condition and/or quality.

Abbreviation and Acronym:

ADR = Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS = Chemical Abstracts Service (division of the American Chemical Society)

CLP = Classification, Labelling and Packaging

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

ICAO = International Civil Aviation Organization

IMDG = International Maritime Code for Dangerous Goods

LD50 = Lethal Dose

LC50 = Lethal Concentration

RID = Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

R-Phrases = Risk Phrases

S-Phrases = Safety Phrases

Annex: Exposure Scenario(s)

Development of Exposure Scenario is not required